

# i5 Weighing Indicator

*A premium quality weighing indicator with a high-speed and accurate AD converter.*



## ABOUT PRODUCT

i5 weighing indicator is a high quality weighing indicator with high speed and precision AD converter.

Having a wide application area, I5 is suitable for use in many areas such as truck scales, platform scales, tank weighing and test equipment.

The i5, which has OIML R76 and European type approval certificates, allows more precise weighing with its two-stage weighing feature.

LED illuminated wide angle 50mm high LCD screen can be mounted on desktop and wall with its flexible mounting design.

It has Kg-Lt-Lb cycle and piece counting etc. features.

## APPLICATION AREAS



Agriculture And  
Livestock



Logistics And  
Transport



Food



Machinery And  
Industry

## TECHNICAL SPECIFICATIONS

Accuracy Class	1/30000
EU Type Approval	(III) n=10.000 Multi-Divisions
Display	51mm LCD with Backlight
Status Displays	10 pcs Status LEDs
Keypad	7 Mechanical switch buttons
ADC	$\Delta$ - $\Sigma$ Delta-Sigma 24 bits
Resolution	0.9 $\mu$ V/e, Legal Approved: 1/10.000 Non-Approved: 1/30.000
Input	-15mV ~ +15mV Input Interval
Linearity & TC	0.01% of Maximum Capacity
Excitation Voltage	5V DC Max 150mA:
Load Cell Count	Max 8 x 350 $\Omega$
Connection Type	4-wires or 6-wires
Kalibrasyon	2 Point, Multi-Stage
Filter	Digital Vibration Filter
Weighing Operations	Tare, Zero, Auto Tare, Auto Zero Auto Clear, Accumulation M+
RTC	Real Time Date and Clock
Zero at Opening	$\pm$ 10% of Max.
Zero Interval	$\pm$ 2% of Max
Tare Interval	Full Capacity Tare
Weight Units	Kg, g, lb, PCS
Serial Ports	Com1 - Rs232/Rs485
Power Supply	External AC Adapter: AC100~240V, DC9V/0.6A